

**New**



The Ingersoll Rand mini tool range is ultra small and light with plenty of power. It easily fits in the palm of anyone's hand and is ideal for tight spaces and fine details work.

- 68 Nm (50 ft-lb) of maximum torque in reverse.
- Swinging hammer impact mechanism is well-suited to wide range of air pressures.
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort.
- Feather-touch trigger allows precise delivery of power and speed.
- One-hand forward/reverse switch for easy operation.
- Through-handle exhaust directs air away from the operator.
- Silenced through-handle exhaust reduces the noise level.
- The small size of this tool will allow greater access to tight spaces.
- The low weight of this tool will reduce operator fatigue.

## Specifications at 6,2 bar (90 psi)

Part Number	2102XP
Ordering number	16619686
Drive size (square)	3/8 in
Available versions:	
- 1/4" hex drive	2101XP-QC
- 1/4" square drive	2101XP

## PERFORMANCE

Working torque in forward	25 - 40 ft-lb / 34 - 54 Nm
Maximum torque in forward	45 ft-lb / 61 Nm
Maximum torque in reverse	50 ft-lb / 68 Nm
Recommended fastener size	5/16 in / M8
Free speed	11 000 rpm
Impacts per minute	1 250

## AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	1,8 CFM / 50 L/min
Air consumption at load	18,2 CFM / 515 L/min

## NOISE & VIBRATION

Impacting sound pressure / power (ISO15744)	85,8 / 96,8 dB(A)
Free speed sound pressure / power (ISO15744)	81,8 / 92,8 dB(A)
Vibration level / measurement uncertainty (ISO28927)	4,4 / 0,8 m/s <sup>2</sup>

## WEIGHT & DIMENSIONS

Tool weight	1,39 lb / 0,63 kg
Tool dimensions (L x W x H)	165 x 127 x 45 mm
Shipping weight	1,94 lb / 0,88 kg
Shipping dimensions (L x W x H)	242 x 143 x 57 mm
UPC / EAN code	6 63023 08352 0
Origin	Made in Japan

[www.ingersollrandproducts.com](http://www.ingersollrandproducts.com)

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

© 2008 Ingersoll-Rand Company — Form No. PDS\_2102XP\_EN\_22/11/2010



**SK3M10**  
81287344  
3/8" Impact socket set (10 pcs) (9, 10, 11, 12, 13, 14, 15, 16, 17 and 19 mm)



**Impact sockets**  
For the complete range, see our accessory catalogue.



**IB6NMC2**  
88103015  
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



**77NMC2**  
88104070  
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7,2 - 7,4)



**Couplings**  
For the complete range, see our accessory catalogue.



**Filters, regulators, lubricators**  
For the complete range, see our accessory catalogue.



**115-LBK1**  
04616108  
Lubricant kit for Impacttools™ with composite housing



**10Z4**  
03875671  
Oil, Class 1, no. 10, 0,12 L



**115-4T-6**  
04618948  
Grease for Impacttools with composite housing (6 tubes)



**Lubricants**  
For the complete range, see our accessory catalogue.