



Designed for conveniences, the 327-EU make it the ideal tool for every tire shop.

- Powerful motor delivers 0.38 kW (0.50 HP).
- 22 000 rpm free speed.
- Variable-speed lever allows precise delivery of power and speed.
- Rear exhaust directs air away from the operator.
- Optional piped-away exhaust system can further reduce noise level and directs air away from the operator.

Specifications at 6.2 bar (90 psi)

Part Number	327-EU
Ordering number	01343771
Chuck capacity	3/8 in / 10 mm
Spindle size	3/8"-24

PERFORMANCE

Rated power	0.50 HP / 0.38 kW
Free speed	22 000 rpm

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	15.0 CFM / 425 L/min
Air consumption at load	26.6 CFM / 12.6 L/s

NOISE & VIBRATION

Sound pressure / power (ISO15744)	87.9 / 98.9 dB(A)
Vibration level / measurement uncertainty (ISO28927)	4.6 / 1.1 m/s²

WEIGHT & DIMENSIONS

Tool weight	1.61 lb / 0.73 kg
Tool length	224 mm
Shipping weight	3.5 lb / 1.6 kg
Shipping dimensions (L x W x H)	230 x 220 x 60 mm
UPC / EAN code	N/A
Origin	Made in Taiwan





7802-99
03789567
Standard chuck, 10 mm



R000B2J70-J253
03095023
Key for standard chuck, 10 mm



LA410-HA1
56752363
Piped-away exhaust kit



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Quick Release Couplings
For the complete range, see our accessory catalogue.



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



Lubricants
For the complete range, see our accessory catalogue.