



Designed for conveniences, the 327LS make it the ideal tool for every tire shop.

- Powerful motor delivers 0.38 kW (0.50 HP).
- 3 000 rpm free speed.
- Convenient hanger-keeps tool within easy reach.
- Integral trigger safety lock prevents accidental tool start.
- Rear exhaust directs air away from the operator.
- Piped-away exhaust system further reduces noise level and directs air away from the operator.

Specifications at 6.2 bar (90 psi)

Part Number	327LS
Ordering number	01371699
Chuck size (hex.)	7/16 in

PERFORMANCE

Rated power	0.50 HP / 0.38 kW
Free speed	3 000 rpm

AIR SYSTEM

Air Inlet (NPT)	1/4 in
Minimum hose size	3/8 in / 10 mm
Average air consumption	14.0 CFM / 396 L/min
Air consumption at load	26.7 CFM / 12.6 L/s

NOISE & VIBRATION

Sound pressure / power (ISO15744)	92.0 / 103.0 dB(A)
Sound pressure / power with piped-away exhaust system (ISO15744)	77.4 / 88.4 dB(A)
Vibration level / measurement uncertainty (ISO28927)	< 2.5 / - m/s²

WEIGHT & DIMENSIONS

Tool weight	1.1 lb / 0.50 kg
Tool length	216 mm
Shipping weight	3.5 lb / 1.6 kg
Shipping dimensions (L x W x H)	230 x 220 x 60 mm
UPC / EAN code	6 63023 01076 2
Origin	Made in Taiwan





BMDS-2
92842152
Cable balancer, 1-2.5 kg, 2 m (6-1/2 ft)



7802-99
03789567
Standard chuck, 10 mm



IB6NMC2
88103015
IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



Quick Release Couplings
For the complete range, see our accessory catalogue.



10Z4
03875671
Oil, Class 1, no. 10, 0.12 L



728-99-KC5
04276564
Keyless chuck, 10 mm



R000B2J70-J253
03095023
Key for standard chuck, 10 mm



77NMC2
88104070
7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Filters, regulators, lubricators
For the complete range, see our accessory catalogue.



Lubricants
For the complete range, see our accessory catalogue.