

4152-HL-SR

75 mm (3") random orbital sander



This vacuum-ready, low-vibration model produces an ultra high-quality finish and connects to central or portable vacuum systems. The 4152-HL-SR extracts dust and particles through and around the pad, keeping foreign matter away from the motor. Virtually all dust is instantly channeled away from the work.

- Powerful motor delivers 0.15 kW (0.20 HP) and produces the best speed under load for swirl-free finish.
- 75 mm (3") pad size is ideal for spot repair.
- 2.5 mm (3/32") orbit for excellent surface finishing.
- Fully machined counterweight significantly reduces vibration and greatly increase service life.
- Advanced composite rotor and vanes allow for non-lube, oilfree operation.
- Lightweight composite housing makes this sander the lightest tool in its class.
- Wide range of power regulator settings helps adjusting the power to the application.
- Vacuum-ready it connects easily to central or portable vacuum systems through a 360° swivel.

Specifications at 6.2 bar (90 psi)

Part Number	4152-HL-SR
Ordering number	16674301
Pad diameter	3 in / 75 mm
Orbit diameter	3/32 in / 2.5 mm
Spindle size	5/16-24
- 150 mm (3") pad size, 5 mm (3/16") orbit	4151-HL
- 150 mm (3") pad size, 5 mm (3/16") orbit, long handle	4151-HL-2
- 150 mm (3") pad size, 2.5 mm (3/32") orbit	4152-HI

PERFORMANCE

 Rated power
 0.20 HP / 0.15 kW

 Free speed
 12 000 rpm

AIR SYSTEM

Air Inlet (NPTF)

Air Inlet (NPTF)

Minimum hose size

5/16 in / 8 mm

Average air consumption

Air consumption et free speed

Air consumption at load

15.5 CFM / 430 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)

**Vibration level / measurement uncertainty (ISO28927)

**A.7 / 1.3 m/s²

WEIGHT & DIMENSIONS

 Tool weight
 1.85 lb / 0.84 kg

 Shipping weight
 2.93 lb / 1.33 kg

 Shipping dimensions (L x W x H)
 205 x 165 x 115 mm

 UPC / EAN code
 6 63023 06622 6

 Origin
 Made in China





Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.





4152-HL-SR

ACCESSORIES



010056 15969223

75 mm (3") hook-and-loop pad, vacuum



4151JV

04662896

Jet-Vac conversion kit



49988

04324455

Dust collection bags (20 pcs)



49987

04324448

Dust collection bags (250 pcs)



49801

04248571

Rubber grip, small size



49798

04248555

Rubber grip, medium size



49799

04248563

Rubber grip, large size



49840

04252938

Rubber grip (3 pcs), small, medium and large sizes



IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Quick Release Couplings

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



10**Z**4

03875671

Oil, Class 1, no. 10, 0.12 L



Lubricants

For the complete range, see our accessory catalogue.



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

