



**This vacuum-ready, low-vibration model produces an ultra high-quality finish and connects to central or portable vacuum systems. The 4151-HL-2 extracts dust and particles through and around the pad, keeping foreign matter away from the motor. Virtually all dust is instantly channeled away from the work.**

- Powerful motor delivers 0.15 kW (0.20 HP) and produces the best speed under load for swirl-free finish.
- 5 mm (3/16") orbit for general sanding.
- Fully machined counterweight significantly reduces vibration and greatly increase service life.
- Advanced composite rotor and vanes allow for non-lube, oil-free operation.
- Lightweight composite housing makes this sander the lightest tool in its class.
- Wide range of power regulator settings helps adjusting the power to the application.
- Vacuum-ready it connects easily to central or portable vacuum systems through a 360° swivel.



### Specifications at 6.2 bar (90 psi)

Part Number	4151-HL-2
Ordering number	22041198
Pad diameter	5 in / 150 mm
Orbit diameter	3/16 in / 5 mm
Spindle size	5/16-24
- 150 mm (3") pad size, 5 mm (3/16") orbit	4151-HL
- 150 mm (3") pad size, 5 mm (3/16") orbit, long handle	4151-HL-2
- 150 mm (3") pad size, 2.5 mm (3/32") orbit	4152-HL
- 75 mm (3") pad size, 2.5 mm (3/32") orbit	4151-HL-SR

### PERFORMANCE

Rated power	0.20 HP / 0.15 kW
Free speed	12 000 rpm

### AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	5/16 in / 8 mm
Average air consumption	8.0 CFM / 220 L/min
Air consumption at free speed	16.0 CFM / 448 L/min
Air consumption at load	15.5 CFM / 430 L/min

### NOISE & VIBRATION

Sound pressure / power (ISO15744)	81.6 / 92.6 dB(A)
Vibration level / measurement uncertainty (ISO28927)	6.2 / 1.0 m/s <sup>2</sup>

### WEIGHT & DIMENSIONS

Tool weight	2.46 lb / 1.12 kg
Shipping weight	3.36 lb / 1.63 kg
Shipping dimensions (L x W x H)	260 x 165 x 115 mm
UPC / EAN code	6 63023 01556 9
Origin	Made in China



[www.ingersollrandproducts.com](http://www.ingersollrandproducts.com)

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.



**49835**  
04250171  
150 mm (6") hook-and-loop pad,  
vacuum



**49988**  
04324455  
Dust collection bags (20 pcs)



**49801**  
04248571  
Rubber grip, small size



**49799**  
04248563  
Rubber grip, large size



**IB6NMC2**  
88103015  
IBN/IBS Series nipple, 1/4" male  
thread, 6 mm bore (ISO6150B / MIL-  
C4109)



**Quick Release Couplings**  
For the complete range, see our  
accessory catalogue.



**10Z4**  
03875671  
Oil, Class 1, no. 10, 0.12 L



**4151JV**  
04662896  
Jet-Vac conversion kit



**49987**  
04324448  
Dust collection bags (250 pcs)



**49798**  
04248555  
Rubber grip, medium size



**49840**  
04252938  
Rubber grip (3 pcs), small, medium  
and large sizes



**77NMC2**  
88104070  
7N7/7S7 Series nipple, 1/4" male  
thread, 7.2 mm bore (EURO 7.2 - 7.4)



**Filters, regulators, lubricators**  
For the complete range, see our  
accessory catalogue.



**Lubricants**  
For the complete range, see our  
accessory catalogue.